

## NOTES

1. THE EXISTING CLAIMANT'S CORNERS WERE RECOVERED AND USED TO CONTROL THE LOCATION OF THE TRACT BOUNDARIES.
2. THIS SURVEY WAS ACCOMPLISHED IN ACCORDANCE WITH OTE SI 88-192, AND AS 38.05.077.. (SLA 1978).
3. THE MINIMUM CLOSURE OF THE TRACT BOUNDARIES AND THE MINIMUM ACCURACY OF THE FIELD SURVEYED TIE TO THE BASIS OF COORDINATES, AS FIELD MONUMENTED, EXCEEDS 1:5000.
4. ALL BEARINGS SHOWN ARE TRUE BEARINGS AS ORIENTED TO THE BASIS OF BEARING, AND DISTANCES SHOWN ARE REDUCED TO HORIZONTAL FIELD DISTANCES.
5. ALL PARCELS ON LANDS OWNED BY THE STATE OF ALASKA, LOCATED WITHIN FIFTY (50.00) FEET OF, OR BISECTED BY A SURVEYED SECTION LINE, ARE SUBJECT TO A FIFTY (50.00) FOOT EASEMENT, EACH SIDE OF THE SECTION LINE, WHICH IS RESERVED TO THE STATE OF ALASKA FOR PUBLIC HIGHWAYS UNDER A.S. 19.10.010.

## LEGEND

⊕ SET FLANGED, MAGNETIZED ALUMINUM MONUMENT 3-1/4" CAP, 2-3/8" o.d. PIPE, 30" LONG, BURIED 26" DEEP.

⊕ PRIMARY MONUMENT RECOVERD

———— SURVEYED

— — — — UNSURVEYED

(R) RECORD FROM PLAT NO. 81-1, (SEE SOURCE NOTE)

(R1) RECORD FROM PLAT OF ASLS 86-251, PLAT NO. 88-16, FILED NOVEMBER 16, 1988, B.B.R.D.

(F) FOUND