

LEGEND



RECOVERED BLM BRASS CAP MONUMENT.



RECOVERED IDITAROD TRAIL LOCATION MONUMENT.



SET PRIMARY MONUMENT (REFER TO NOTE 1).

———— SURVEYED

----- UNSURVEYED

MEANDERS

<u>NO.</u>	<u>BEARING</u>	<u>DISTANCE</u>	<u>NO.</u>	<u>BEARING</u>	<u>DISTANCE</u>
30	S 87° 43' 13" E	187.03'	49	S 74° 44' 53" W	55.99'
31	S 65° 48' 42" E	84.07'	50	S 65° 17' 35" W	78.00'
32	N 59° 27' 18" E	140.97'	51	S 29° 36' 04" W	76.93'
33	N 8° 27' 18" W	119.38'	52	N 80° 30' 39" W	75.79'
34	N 57° 54' 05" E	56.30'	53	S 77° 10' 11" W	85.30'
35	S 46° 27' 08" E	84.94'	54	S 44° 50' 21" W	159.29'
36	S 78° 20' 18" E	145.40'	55	S 6° 46' 14" W	130.01'
37	N 60° 53' 08" E	54.03'	56	S 57° 38' 07" W	117.63'
38	N 3° 13' 13" W	106.34'	57	S 36° 23' 44" W	173.05'
39	N 20° 44' 05" W	41.98'	58	S 86° 42' 03" W	73.99'
40	N 54° 01' 04" E	60.07'	59	N 72° 06' 27" W	82.08'
41	S 47° 46' 16" E	132.57'	60	N 48° 29' 20" E	64.84'
42	S 80° 51' 05" E	78.87'	61	N 7° 11' 19" E	161.13'
43	N 37° 55' 28" E	74.80'	62	N 53° 49' 14" W	72.88'
44	N 23° 30' 52" E	143.98'	63	S 89° 20' 59" W	91.69'
45	S 76° 49' 44" E	39.68'	64	N 69° 37' 57" W	102.46'
46	S 49° 47' 25" E	87.30'	65	S 87° 53' 24" W	69.45'
47	S 17° 40' 15" E	90.46'	66	N 74° 23' 56" W	110.57'
48	S 31° 36' 50" W	118.37'	67	N 29° 07' 28" W	50.12'
			68	N 66° 46' 12" E	148.99'

NOTES

1. SET FLANGED, MAGNETIZED ALUMINUM MONUMENT 3-1/4" CAP. 2-3/8" o.d. PIPE, 30" LONG, BURIED 26" DEEP, EXTENDS ABOUT 4" ABOVE GROUND.
2. THIS SURVEY WAS ACCOMPLISHED IN ACCORDANCE WITH RP-SI-95-16, AND AS 38.05.077., (SLA19B1)
3. THE EXISTING CLAIMANT CORNERS WERE RECOVERED AND USED TO CONTROL THE LOCATION OF THE TRACT BOUNDARIES.
4. THE MINIMUM CLOSURE OF THE TRACT BOUNDARIES AND THE MINIMUM ACCURACY OF THE FIELD SURVEYED TIE TO THE RECTANGULAR SURVEY SYSTEM, AS FIELD MONUMENTED, EXCEEDS 1:5000.
5. ALL BEARINGS SHOWN ARE TRUE BEARINGS AS ORIENTED TO BASIS OF BEARING, AND DISTANCES SHOWN ARE REDUCED TO HORIZONTAL FIELD DISTANCES.
6. ALL PARCELS ON LAND OWNED BY THE STATE OF ALASKA, LOCATED WITHIN FIFTY (50.00) FEET OF, OR BISECTED BY A SURVEYED OR PROTRACTED SECTION LINE, ARE SUBJECT TO A FIFTY (50.00) FOOT EASEMENT, EACH SIDE OF THE SECTION LINE, WHICH IS RESERVED TO THE STATE OF ALASKA FOR PUBLIC HIGHWAYS UNDER A.S. 19.10.010
7. THE NATURAL MEANDERS OF THE LINE OF ORDINARY HIGH WATER FORM THE TRUE BOUNDS OF THE TRACTS. THE APPROXIMATE LINE OF ORDINARY HIGH WATER AS SHOWN, IS FOR AREA COMPUTATIONS ONLY, WITH THE TRUE TRACT CORNERS BEING ON THE EXTENSION OF THE TRACT SIDE LINES AND THEIR INTERSECTION WITH THE NATURAL MEANDERS.
8. ALL WASTEWATER DISPOSAL SYSTEMS, INCLUDING PIT PRIVIES, MUST BE LOCATED A MINIMUM OF ONE HUNDRED (100) FEET FROM STREAMS OR WATER BODIES.