

LEGEND

- ⊕ SET 2 1/2" X 30" ALUMINUM MONUMENT
- ⊕ SET 2 1/2" ALUMINUM CAP ON 3/4" DRIVE ROD
- ⊕ BLM MONUMENT RECOVERED
- SET 2" ALUMINUM CAP ON 5/8" X 30" REBAR
- FND 2 1/2" ALUMINUM MONUMENT
- BOUNDARY LINE OF THIS SURVEY
- OTHER SURVEYED LINE, INCLUDING TIE LINE
- EASEMENT LINE
- APPROXIMATE BOUNDARY LINE OF OTHER LEASE

TR = TRACT C = COMPUTED REC = RECORD MON = MONUMENT

BLM = BUREAU OF LAND MANAGEMENT Meas = Measured

ASLS = Alaska State Land Survey

NOTES



1. THIS SURVEY WAS ACCOMPLISHED IN ACCORDANCE WITH REMOTE PARCEL SPECIAL SURVEY INSTRUCTIONS NO. 86-86 AND WITH A.S. 38.05.077 (SLA 1981)
2. ALL PARCELS OF LAND OWNED BY THE STATE OF ALASKA LOCATED WITHIN 50.00 FEET OF, OR BISECTED BY, A SURVEYED SECTION LINE ARE SUBJECT TO A 50.00 FOOT EASEMENT EACH SIDE OF THE SECTION LINE WHICH IS RESERVED TO THE STATE OF ALASKA FOR PUBLIC HIGHWAYS UNDER A.S. 19.10.010.
3. ALL CLAIMANTS' CORNERS WERE RECOVERED AND USED TO CONTROL THE LOCATION OF THE TRACT BOUNDARIES.
4. A SUNSHOT WAS COMPLETED TO CHECK BLM RECORD. THIS AGREED WITHIN 02 INCHES WITH BLM RECORD.
5. ALL LINES ALONG YENTNA RIVER ARE SET BACK A MINIMUM OF 100' FROM THE OHW LINE.
6. THE MINIMUM CLOSURE OF THE TRACT BOUNDARIES AND THE MINIMUM ACCURACY OF THE FIELD SURVEYED TIE TO THE BASIS OF COORDINATES, AS FIELD MONUMENTED, MEETS OR EXCEEDS ONE PART IN FIVE THOUSAND, (1:5000)
7. ALL DISTANCES SHOWN HEREON ARE REDUCED TO HORIZONTAL FIELD DISTANCES.
8. ALL BEARINGS SHOWN ARE "PLANE" BEARINGS AS ORIENTED TO THE BASIS FOR BEARINGS.
9. ALL TRACTS ARE SUBJECT TO A 25 FOOT PUBLIC ACCESS EASEMENT ALONG ALL UPLAND BOUNDARY LINES.