











NOTES (APPLIES TO ALL SHEETS)

1. This survey was executed under the terms of GSC-556.
2. Unless noted otherwise, all bearings shown hereon are based on a local plane which is oriented to true meridian at the Basis of Bearing. The Basis of Bearing for this survey is the Township line common to Sections 6, 7 and 18, Township 11 South, Range 57 West and Sections 1, 12 and 13, Township 11 South, Range 58 West shown as North on the B.L.M. plats of record for the original cadastral survey of said townships.
3. Unless noted otherwise, all distances shown hereon are in U.S. survey feet, adjusted to horizontal but not to sea level distances.
4. Record dimensions and bearings appear in parentheses and are taken from the survey plats of record as noted.
5. All parcels on lands owned by the State of Alaska, located within fifty (50.00) feet of, or bisected by a surveyed section line, are subject to a fifty (50.00) foot easement, each side of the section line, which is reserved to the State of Alaska for public highways under A.S. 19.10.010.
6. The titles, ALASKA DIVISION OF LANDS (ADL), DIVISION OF TECHNICAL SERVICES (DTS), AND DEPARTMENT OF NATURAL RESOURCES (DNR), are synonymous.
7. Parcels within this subdivision may contain wetlands as defined within the purview of Section 404 of the Clean Water Act, and may require Department of Army Corps of Engineers (COE) permits prior to placement of fill material into these areas. Contact with COE must be made prior to commencing construction.
8. Water Supply and Sewage Disposal: No individual water supply system or sewage disposal system shall be permitted on any lot unless such system is located, constructed and equipped in accordance with the requirements of the Alaska Department of Environmental Conservation (ADEC). Approval of such systems shall be obtained from said authority.
9. This subdivision has been approved by the ADEC pursuant to 18 AAC 72.065 for pit privy sewage disposal systems only. Installation of other types of sewage disposal systems will require an on-site inspection by a professional engineer, and approval, construction, and operation in compliance with all applicable ADEC requirements.

10. The meanders of Lake Nunavugeluk are for area computation purposes only, and the true meanders of mean high water or ordinary high water form the boundaries of the lots.
11. Unless otherwise shown: there is a ten foot (10') utility easement each side of common interior lot and tract lines. There is a twenty foot (20') utility easement located adjacent to right-of-way lines within all lots and tracts. There shall be easements as required at each pole location for guys and anchors. The right shall be reserved for the involved utility companies to cut any trees, within or without the easement, which reasonably present a danger to the utility.
12. Screening easements fifty (50.00) feet in width are created along all watercourses within this subdivision draining into Lake Nunavugeluk. Said screening easements shall be centered on the watercourse thread. Said screening easements shall be preserved in their natural state and no clearing or construction shall be allowed within said easement.
13. No part of a subsurface sewage disposal system shall be closer than one hundred feet (100') from any body of water or watercourse.
14. The accuracy of this survey is greater than 1:5000.
15. Public access across state owned tracts may be obtained by application to the District Office of the Department of Natural Resources.
16. Unless otherwise noted, all lands encompassed by this survey are subject to a fifty (50.00) foot wide access easement along the mean high water or ordinary high waterline of any public or navigable water pursuant to A.S. 38.04.055 and A.S. 38.05.127.

LEGEND (APPLIES TO ALL SHEETS)

-  - GLO - BUM MONUMENT RECOVERED
-  - PRIMARY ALUMINUM CAP MONUMENT SET (DTS)
-  - SECONDARY MONUMENT SET (DTS) AT ALL OTHER CORNERS
-  - ORDINARY HIGH WATER MEANDER LINE
-  - RECORD DIMENSION -- SOURCE NOTED
-  - INDICATES TANGENT OR MEANDER TABLE IDENTIFIER
-  - INDICATES CURVE TABLE IDENTIFIER
-  - INDICATES NON-RADIAL LOT OR TRACT LINE
-  - INDICATES SHEET MATCH LINE
-  - INDICATES WITNESS CORNER TO MEANDER CORNER

MEANDER TABLE

LABEL	BEARING	DISTANCE
T1	S 35° 34' 37" E	407.65
T2	S 22° 24' 05" E	411.66
T3	S 14° 07' 19" E	281.27
T4	S 12° 23' 45" M	300.73
T5	S 21° 26' 23" M	421.01
T6	S 17° 34' 40" M	278.33
T7	S 15° 12' 24" M	333.90
T8	S 0° 16' 05" M	266.91
T9	S 03° 22' 17" M	106.13
T10	S 12° 55' 33" E	143.48
T11	S 26° 57' 24" E	304.98
T12	S 41° 07' 40" E	241.87
T13	S 54° 03' 52" E	290.09
T14	S 64° 49' 44" E	135.98
T15	S 81° 12' 55" E	119.65
T16	N 70° 33' 09" E	81.95
T17	N 43° 59' 46" E	99.30
T18	N 30° 37' 36" E	105.84
T19	N 47° 36' 22" E	96.28
T20	N 53° 39' 17" E	116.33
T21	N 60° 56' 15" E	117.51
T22	N 66° 13' 30" E	107.38
T23	S 63° 11' 35" E	169.78
T24	S 54° 01' 09" E	190.14
T25	S 39° 57' 40" E	171.48
T26	S 35° 19' 16" E	181.78
T27	S 34° 33' 46" E	265.97
T28	S 33° 56' 46" E	332.72
T29	S 40° 13' 06" E	76.60
T30	S 48° 30' 09" E	376.29
T31	S 35° 29' 41" E	85.52
T32	S 20° 26' 43" E	182.02
T33	S 13° 57' 28" E	293.39
T34	S 05° 02' 12" E	306.82
T35	S 02° 09' 46" M	123.44
T36	S 23° 35' 46" E	121.12
T37	S 10° 00' 45" E	74.00
T38	S 21° 24' 50" M	199.91
T39	S 13° 07' 07" M	126.72
T40	S 08° 53' 44" E	222.43
T41	S 08° 28' 29" M	402.13
T42	S 06° 42' 05" M	333.39
T43	S 00° 20' 16" M	184.04
T44	S 11° 43' 41" E	188.57
T45	S 10° 46' 58" E	182.87
T46	S 37° 56' 57" E	96.12
T47	S 37° 01' 26" E	157.47
T48	S 19° 05' 28" E	237.42
T49	S 12° 56' 49" E	370.42
T50	S 28° 23' 05" E	105.61
T51	S 40° 19' 23" E	170.31
T52	S 39° 11' 07" E	309.34
T53	S 38° 35' 06" E	431.05
T54	S 58° 18' 07" E	319.78
LABEL	BEARING	DISTANCE