## NOTES

- THE EXISTING CLAIMANT'S CORNERS WERE RECOVERED AND USED TO CONTROL THE LOCATION OF THE TRACT BOUNDARIES.
- THIS SURVEY WAS ACCOMPLISHED IN ACCORDANCE WITH HE-SI 92-72, AND A.S. 38.09.010, (\$LA 1983, AM. 1984)
- 3. THE MINIMUM CLOSURE OF THE TRACT BOUNDARY AND THE MINIMUM ACCURACY OF THE FIELD SURVEYED TIE TO THE BASIS OF COORDINATES, AS FIELD MONUMENTED, EXCEEDS 1:5,000.
- 4. ALL BEARINGS SHOWN ARE TRUE BEARINGS AS ORIENTED TO THE BASIS OF BEARING, AND DISTANCES SHOWN ARE REDUCED TO HORIZONTAL FIELD DISTANCES.
- 5. ALL PARCELS ON LANDS OWNED BY THE STATE OF ALASKA, LOCATED WITHIN FIFTY (50,00) FEET OF, OR BISECTED BY A SURVEYED SECTION LINE, ARE SUBJECT TO A FIFTY (50,00) FOOT EASEMENT, EACH SIDE OF THE SECTION LINE, WHICH IS RESERVED TO THE STATE OF ALASKA FOR PUBLIC HIGHWAYS UNDER A.S. 19.10,010.
- MONUMENTS ARE STAMPED WITH "ASLS 92-72" ON TOP AND "LS 4802" AND "1992" ON THE BOTTOM.
- 7. THERE MAY BE FEDERAL, STATE AND LOCAL REQUIREMENTS GOVERNING LAND USE. IT IS THE RESPONSIBILITY OF THE INDIVIDUAL PARCEL.
  OWNER TO OBTAIN A DETERMINATION WHETHER SUCH REQUIREMENTS APPLY TO THE DEVELOPMENT OF PARCELS SHOWN HEREON.
- B. ALL LOTS HAVE AT LEAST 20,000 SQ. FEET OF USABLE AREA, AS DEFINED BY MSB ORDINANCE.
- 9. LEGAL ACCESS TO THIS SUBDIVISION HAS NOT BEEN DOCUMENTED AT THE TIME OF RECORDING.
- (Q. SET FLANGED, MAGNETIZED ALUMINUM MONUMENT 2 1/2" CAP, 2 3/8" O.D. PIPE, 30" LONG, BURIED 30" DEEP, EXCEPT CORNERS 4 AND 5 OF TRACT A, WHICH ARE 3 1/4" ALUMINUM CAP ON 3/4" ALUMINUM ROD, 9 FEET LONG, DRIVEN 8 1/2 FEET INTO THE GROUND.
- !!. ALL BEARING TREES ARE BLAZED AND SCRIBED "X BT".
- THERE IS A PUBLIC ACCESS EASEMENT ON THE UNNAMED CREEK AND FOR 50' OUT FROM THE ORDINARY HIGH WATER MARK ON EACH SIDE.
- ANY WASTE WATER SYSTEM, INCLUDING A PRIVY, MUST BE AT LEAST 100' FROM ANY STREAM OR LAKE.

## LEGEND

PRIMARY MONUMENT SET THIS SURVEY

PRIMARY MONUMENT RECOVERED

- --- PUBLIC ACCESS EASEMENT (TYPICAL 30') AND UTILITY

--- SURVEYED LINE

CENTERLINE CREEK

RECORD R

M MEASURED